



<u>PROJECT</u>
<u>CONTACT (NAME/TEL)</u>

Low Voltage Track Lighting Fixture 50164




PRODUCT DESCRIPTION

- 350° horizontal rotation or 90° vertical projecting.
- May be fitted with factory installed extensions.

SPECIFICATIONS

Description	Low Voltage Track Lighting Fixture
Wattage	50W / 75W
Voltage	12V
Light Bulb	MR16 Halogen Lamp - Dimmable with ELV, electronic dimmer. MR16 LED Lamp (minimum of 7W or higher) – Do not use front glass if using LED bulb. Do not dim below 7 watts. Bulb Not Included. Please order separately.
Accessories	Clear front lens and holder clip included.
Finish	Black (BK), White (WH), Brushed Steel (BS), Dark Bronze (DB), Rust (RU).
Construction	<ul style="list-style-type: none"> • Die-cast aluminum track head with polycarbonate transformer case. • GU5.33 Bi-pin ceramic socket for MR16 lamp. • Fixture can be dim with 120V input electronic dimmer. • Integral electronic transformer build-in with the fixture.
Environment	Indoor, Dry Location
Rating	UL &cUL Listed

Compatible Accessories – Order separately

	Factory Installed Low Voltage Extension Wand. Available in 6", 12", 18", 24", 36", 48".
---	--

Ordering Information

System	Model	Watt	Finish
HT*, HT2, JT	50164	50 / 75	WH / BK / BS / DB / RU

**"Pull-up" contact to up position for two-circuit application

Ordering Examples: HT-50164-WH, HT-50164/75W-BS, HT-50164-EX18-BK, JT-50164-DB

Product specification subject to change without notice.